The MixRite 1400 Series is comprised of water powered proportioners that are typically used for greenhouses, cleaning, and sanitizing produce, as well as drip and spray irrigation applications. These injectors have a better compatibility for nutrients, pesticides, some acids, and other additives. The updated internal design allows for an increased flow rate of up to 14 GPM and up to 10% for chemical injection. All 1400 MixRites have a 3/4" NPT threaded inlet and outlet.

Features & Benefits

- Flow rate .5 to 14 GPM
- Hastelloy, and plastic engine springs for improved chemical compatibility
- AFLAS O-Rings throughout the unit
- Viton Extreme chemical seal
- Easy-to-adjust chemical adjustment sleeve
- Low-flow rate engine with dual lip seals can be powered by water flow rates as low as .5 GPM

MODELS

1400A / 1400M – Injection .03 to .2%

1401A / 1400M – Injection .1 to .9%

1402A / 1402M – Injection .2 to 2%

1405A / 1405M – Injection .5 to 5%

1410A / 1410M – Injection 1 to 10%

A – Air release (Standard)

M - Manual On/Off

MixRite Accessories



WATER SUPPLY HOSES

DEMA manufactures a variety of water inlet hoses for different applications. DEMA inlet hoses are rated to 200psi, made of durable double-walled rubber, and crimped to our manufacturing facility specifications.



Compressed Air Foamer and Foam Wand

Compressed Air Foamer and wand can be used with any MixRite, air, and an outlet hose to produce

FoamStation: #294DC.DS Foam Wand: #93.18



Contact for available options



STRAINER

The DEMA 3/4" NPT strainer is an in-line 200 mesh (80 microns) strainer recommended for all MixRite installations. The in-line strainer will keep debris out of the MixRite unit, increasing the life of the seals.



WHITE FOOT VALVE STRAINER

3/4" white foot valve strainer prevents debris from entering the unit through the chemical inlet tubing.

#57.34FT



3/4" CHECK VALVE

The DEMA check valve helps limit backflow situations if the unit is used to pump the mixture any significant distance.

#57.20.8

#50.41.1



3/4" ANTI-SIPHON KIT

For any 3/4" MixRites in-line to relieve pressure so chemical will not siphon out of drum or tank.

#36073008002



UFR - LOW FLOW BOOSTER

The 57.UFR low flow booster works with any 500 series MixRite to take low flows (less than .9gpm) and allows the unit to work in low flow conditions.

#57.UFR



PRESSURE REGULATOR & GAUGE

Fits in-line with any MixRite to limit pressure spikes.

Regulator: #38030200001

Gauge: #93.15.1



Spray Gun and Foam Wand

The DEMA Spray Gun and Foam Wand set is a simple but effective foam application system. Easily connect to a MixRite with a standard garden hose to begin foaming. To rinse off surfaces, simply remove the Foam Wand and use the Spray Gun.

Spray Gun: #28.1QD Foam Wand: #292GQD



DEMA Engineering Company

10020 Big Bend Road St. Louis, MO 63122 U.S.A

Tel: 314-966-3533 Fax: 314-965-8319



ag.demaeng.com

